

# Limiting Amplifier

## 4000-8000MHz

Model Number: OC-LA4-8K40A

The model OC-LA4-8K40A is a broadband, low noise, high gain limiting amplifier operating between 4000 MHz and 8000 MHz and handling a wide dynamic range from -40dBm to +10 dBm. The employment of FET devices with good consistency in manufacturing ensures this module exceptional amplitude limiting performance. It is the key component of the electronic system.

### FEATURES:

- Broadband;
- Low Noise;
- High Gain;
- Small Size & Light Weight;
- Good Consistency;

### ELECTRICAL SPECIFICATIONS @ +12.0VDC, 25°C, 50Ω

Parameter	Symbol	Min	Typ	Max	Units
Operating Frequency	BW	4000		8000	MHz
Input Power	P <sub>in</sub>	-40		+10	dBm
Limited Output Power	P <sub>out</sub>	+13		+17	dBm
Noise Figure	NF		4		dB
Harmonic Rejection	H		12		dBc
VSWR @ Input Port	IN VSWR			2.0:1	
VSWR @ Output Port	OUT VSWR			2.0:1	
In/Output Impedance	Impedance		50		Ω
Operating Voltage	VDC		+12		Volt
DC Current	IDD			400	mA

### MECHANICAL SPECIFICATIONS

Parameter	Value	Units	Notes
Dimensions	90x30x20 [3.54x1.18x0.79]	mm [inch]	Maximum
Weight	150 [0.33]	g [lbs]	Maximum
RF Connectors Input	SMA, Female		
RF Connectors Output	SMA, Female		
DC Interface Connector	Feed-through capacitor		

### ENVIRONMENTAL CHARACTERISTICS (Design to Meet)

Parameter	Minimum	Typical	Maximum	Units	Notes
Operating Temperature	-20		60	°C	
Non-operating Temperature	-40		65	°C	Storage
Relative Humidity (non-condensing)			95	%	

### Absolute Maximum Rating

Input RF drive level without damage	+15 dBm
DC Voltage	+15 V

4000-8000MHz

Model Number: OC-LA4-8K40A

OUTLINE DRAWING (All dimensions in mm [inch])

